Revision: 11 Oct 21 AL0000-0201-000 ECR 004

## AL0000-0201-000 MP Implodable/Explodable Volume Test/Evaluation Procedure

**CERTIFIED** 

## **DSV ALVIN HYDROSTATIC TEST RECORD**

Test no.:	Test date:		_ Test type: External/Internal (circle one)	
Description of	f item tested (make	e/model):		
Serial number	r(s) (or other uniqu	e ID):		
Tested for/ite	m owned by:			
Test pressure (PSI):+300,		00/-0_ Test medium:	Medium temp:	
Test Equipme	ent			
Gauge make:				
Gauge model:	:			
Gauge Serial r				
Calibration da				
Calibration du	ie date:			
Gauge pressu	re range/accuracy:			
_		at enable the target te		nin the middle 2/3
of the gauge i	range. Test facility	gauge shall be calibrate	ed.	
Tost Data		Ctart time at	Cton time at	Hold
Test Data	Droccuro	Start time at	ı.	Hold
Cycle No.	Pressure	full pressure (hhmm)	full pressure (hhmm)	Duration
1	(psi)	(111111111)	(111111111)	(min)
2				
3				
4				
5				
6				
7				
8				
9				
10				
After testing,	visually inspect iter	m(s) for leakage or visib	le signs of external da	amage.
			_	
Note: Leakag	e or visible signs o	<sup>f</sup> external damage shal	l be cause for test fai	lure
Test results (S	SAT/UNSAT):			
Test Operator	r (print):			<del></del>
Signature:		D	Date:	
restracility: _				